National Phase Application based on International Appln. No. PCT/IB2004/002480 Attorney Docket No. 99759-NEW Amdt. dated February 1, 2006

Amendments to the Specification

On page 14, line 12, of the published international application, please replace the heading "Equation 15" with the following heading:

-- Equation 5 --

On page 18, line 4, of the published international application, in Equation 13, please replace the last line, $``\dot{\xi} = \delta_0 \cdot \sqrt{1 - \left(\frac{x_E}{V_p} \cdot \xi\right)^2} \cdot \dot{\delta} \text{ da cui si ha } \dot{\delta}." \text{ with:}$

$$--\dot{\xi} = \delta_0 \cdot \sqrt{1 - \left(\frac{x_E}{V_R} \cdot \xi\right)^2} \cdot \dot{\delta} \quad \text{from which } \dot{\delta} \quad \text{is obtained.} \quad --$$

On page 19, line 4, of the published international application, immediately following Equation 17, please delete the phrase "in quanto, dalle ipotesi fatte, V_R e x_E sono costanti."

On page 19, lines 5-6, of the published international application, please replace "in so far as, form the hypothesis made, V_R and X_E are constant." with:

-- in so far as, from the hypothesis made, V_R and $X_{\scriptscriptstyle\rm E}$ are constant. --

2

ME1\5473671.1

National Phase Application based on International Appln. No. PCT/IB2004/002480 Attorney Docket No. 99759-NEW Amdt. dated February 1, 2006

On page 20 of the published international application, in Equation 20, sub-equation 20.1), please replace

"20.1)
$$\frac{d^2 \xi}{dt^2} = \frac{P_M - \frac{x_E'}{V_R} \cdot \xi \cdot v_t}{\frac{x_E'}{V_R} \cdot T_M} \quad \text{da cui } v_t \text{. Derivando si ha " with:}$$

-- 20.1)
$$\frac{d^2 \xi}{dt^2} = \frac{P_M - \frac{x_E'}{V_R} \cdot \xi \cdot v_t}{\frac{x_E'}{V_R} \cdot T_M}$$
 from which v_t . By differentiating we obtain --

On page 20 of the published international application, in Equation 20, sub-equation 20.2), please replace

"20.2)
$$\frac{d^3\xi}{dt^3} = -\frac{\dot{\xi} \cdot v_t + \xi \cdot \dot{v}_t}{T_M}$$
 avendo posto $\dot{P}_M \approx 0$ e, infine " with

-- 20.2)
$$\frac{d^3\xi}{dt^3} = -\frac{\dot{\xi} \cdot v_t + \xi \cdot \dot{v}_t}{T_M}$$
 having assumed $\dot{P}_M \approx 0$ and, finally --

3

ME1\5473671.1

National Phase Application based on International Appln. No. PCT/IB2004/002480 Attorney Docket No. 99759-NEW Amdt. dated February 1, 2006

Please delete the Abstract of the published international application and replace it with the following rewritten Abstract:

- -- Compensator device, for the stabilisation of electromechanical oscillations destined to provide a reference signal to a voltage regulator device of a synchronous alternator for the delivery of electrical power to a distribution network, said device including:
- first processing means to receive electrical measurement signals representing operative parameters characteristics of said synchronous alternator and/or to generate an electrical signal to be controlled; and a first electrical signal corresponding to a sliding surface of a control of the "sliding modes" type,
- second processing means of the first signal to generate the reference signal so that it has a first order "sliding modes" profile.

- -